


The DS-7604NI/E1/4P/A is Hikvision's latest edition to the fantastically popular DS-76 range of NVRs, this updated version for 2015 has all the great features of the original DS-76 series NVR but now supports PoE+ devices with a total of 120W available via its 4 built-in PoE plug and play ports. The series now sports a new updated record rate allowing for up to 25Mbts recording and lastly now has 4CIF live view and 4 channel playback.

FEATURES:

- Third-party network cameras supported
- Up to 5 Megapixels resolution recording
- HDMI and VGA output at up to 1920×1080P resolution
- 4-ch network cameras can be connected with 25mbps incoming bandwidth
- 1 SATA interface
- Plug & Play with up to 4 independent PoE network interfaces
- Support network detection, including network delay, packet loss, etc
- 4 alarm inputs, 1 alarm output



	DS-7604NI-E1/4P/A
VIDEO / AUDIO INPUT	
IP Video Input	4-ch
Two-Way Audio Input	1-ch, RCA (2.0 Vp-p, 1Ω)
Incoming Bandwidth	25Mbps
Outgoing Bandwidth	80Mbps
Remote Connection	128
VIDEO/ AUDIO OUTPUT	
Recording Resolution	5MP/4MP/3MP/1080P/UXGA/720P/VGA/ 4CIF/DCIF/2CIF/CIF/QCIF
Frame Rate	Main Stream: 50fps
	Sub Stream: 50fps
HDMI / VGA Output	1-ch resolution:
	1920 x 1080P /60Hz, 1600 x 1200 /60Hz, 1280 x 1024 /60Hz, 1280 x 720 /60Hz, 1024 x 768 /60Hz
Audio Output	1-ch, RCA (Linear, 1kΩ)
Playback Resolution	5MP/4MP/3MP/1080P/UXGA/720P/VGA/4CIF/DCIF /2CIF/CIF/QCIF
DECODING	
Live View/ Playback Res	5MP/4MP/3MP/1080p/UXGA/ 720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Capability	4-ch @ 1080P
HARD DISK	
SATA	1 SATA interface for 1 HDD
Capacity	Up to 4TB capacity for each disk
EXTERNAL INTERFACE	
Network Interface	1 RJ-45 10 / 100 / 1000 Mbps self-adaptive Ethernet interface
USB interface	1 × USB 2.0 and 1 × USB 3.0
Alarm in/out	4/1
POE	
Interface	4 independent 100Mbps PoE network interface
Max Power	50W
Supported Standard	AF and AT
GENERAL	
Power Supply	48V DC
Consumption	<pre>≤ 10W (without hard disk and PoE)</pre>
Working Temperature	-10°C ~ +55°C
Working Humidity	10% ~ 90%
Chassis	1U chassis
Dimensions (WxHxD)	315 x 45 x 230mm (12.4" x 1.8" x 9.1")
Weight	≤ 1 Kg (without hard disk)
aneight.	2 T Ky (WILHOUL HARU UISK)

