



Protect your asset

Full HD All-In-One Security Video System



SDH-B73020

4 Channel Full HD DVR Security System

DVR

- 4CH 1080p full high definition recording
- 1TB surveillance class hard drive
- PC and Mac compatible
- Free Android and iOS app for remote viewing
- Backwards compatible with standard analog cameras
- Supports optional Samsung USB WiFi adapter

Camera

- 2 high definition 1080p outdoor bullet cameras
- Wide angle field of view
- 3-Dimensional noise reduction for clear video quality at low light conditions
- True Day & Night with ICR for perfect color reproduction
- IP66 weather resistant
- Night vision up to 82ft (25m)



SDH-B73020




SDR-B73300



SDC-9441BC

Dimensions

Unit : mm (inch)



SDR-B73300

SDC-9441BC

Kit Contents

- DVR (SDR-B73300)
- Camera (SDC-9441BC) 2pcs
- Remote Control / Batteries
- Mouse / Power Adapter / Power Cord
- 60ft BNC Camera Cable 2pcs
- CD (Smart Viewer, User Manual)
- Quick Start Guide / Network Cable
- HDMI Cable

SDR-B73300N

DISPLAY			
Video	Inputs	4CH BNC	
	Resolution	1920 x 1080 (Full HD) / 1280 x 720 (HD) / 928 x 480 (WD1)	
	Frame Rate	120fps@1920 x 1080 / 120fps@1280 x 720 / 120fps@928 x 480	
Live	Resolution	1920 x 1080 (Full HD) / 1280 x 720 (HD) / 928 x 480 (WD1)	
	Multi Screen Display	1 / 4 / Sequence / PIP	
PERFORMANCE			
Operating System	Embedded	Linux	
	Compression	H.264	
	Record Rate	Up to 120fps@1920 x 1080 / Up to 120fps@1280 x 720 / Up to 120fps@960 x 480	
Recording	Mode	Manual, Schedule (Continuous / Event), Event (Pre / Post), Time lapse (1 ~ 30fps)	
	Event	Video loss, Motion (Sensitivity level 1 ~ 10), Tampering	
	Overwrite Modes	Continuous	
	Pre-alarm	Off / 5sec	
	Post-alarm	Up to 6hour (5,10, 20, 30sec, 1, 3, 5, 10, 20min, 1, 2, 3, 4, 5, 6hour)	
	Search Mode	Date/Time, Event, Back up, Motion (*All search included preview function)	
Search & Playback	Playback Function	Fast forward / backward (2x, 4x, 8x, 16x, 32x, 64x) *Backward plays with I-frame only	
		Slow forward / backward (1/2x, 1/4x, 1/8x)	
		Step forward / backward *Backward play with I-frame only	
Network	Transmission Speed	4CIF 120fps / 2CIF 240fps / CIF 240fps	
	Bandwidth / Bandwidth Control	Up to 32Mbps / Selectable	
	Live Stream	H.264 (4CIF / 2CIF / CIF selectable)	
	Max. Remote Users	Search 3 / Live unicast 10 / Live multicast 20	
	Protocol Support	TCP/IP, UDP/IP, DHCP, PPPoE, SMTP, NTP, HTTP, DDNS, RTP, TSP, UPnP	
	Monitoring	SmartViewer, Webviewer, Mobile Viewer	
Smart Phone	Web / App viewer	Supported OS - PC : Windows XP / VISTA / 7 / 8, MAC OS X 10.7 / 10.9 - Mobile : Android OS v.2.3.5, v4.0.3, v4.1.2, 4.2, v4.3 / IOS OS v5.1.1, v6.0, v6.0.2, v6.1, v7.0, v8.0	
		Supported Browser - Microsoft Internet Explorer (Ver. 11, 10, 9, 8, 7), Mozilla Firefox (Ver. 19, 18, 17, 16, 15, 14, 13, 12, 11, 10, 9), Google Chrome (Ver. 25, 24, 23, 22, 21, 20, 19, 18, 17, 16, 15), Apple Safari (v5.1, v6.1, v7.0) *Mac OS version 10.7 and higher	
		Protocol Support	RTP, RTSP, HTTP, CGI
		Transmission Speed	CIF Max. 16fps (Single channel) / CIF Max. 4fps (Quad channel)
		Max. Remote Users	Live 2 / Search 1
		Internal HDD	1 SATA HDD (1TB)
Storage	USB (Back up)	2 USB ports	
	File Format (Back up)	BU (DVR player), SEC (Include player), AVI	
Security	Password Protection	1 Admin, 10 Group, 10 User per 1 group	
	Data Authentication	Digital watermark	
INTERFACE			
Monitors	VGA / HDMI	1 VGA (1280 x 720, 1280 x 1024, 1920 x 1080) 50/60Hz / 1 HDMI (1280 x 720, 1280 x 1024, 1920 x 1080) 50/60Hz	
	Simultaneous Output	VGA and HDMI	
Audio	Inputs / Output	1CH line in / 1CH line out	
	Compression	G.711, 8KHz	
Alarm	Remote Notification	Notification via e-mail	
	Ethernet	1 RJ-45 10/100 Base-T	
Connections	Serial Interface	RS-485	
	USB	USB 2.0, 2 ports (Front / Rear)	
	Wi-Fi	With optional Samsung Wi-Fi USB adapter	
	Application Support	Mouse, Remote controller, Wi-Fi USB adapter	
	Protocol Support	Samsung-T/E, Pelco-D/P, Panasonic, Phillips, AD, Vicon, GE	
	Coax Protocol	Pelco-C	
GENERAL			
Electrical	Input Voltage / Current	12V DC adapter, 100 ~ 250V AC, 50/60Hz	
	Power Consumption	Max. 12W	
Environmental	Operating Temperature / Humidity	+0°C ~ +40°C (+32°F ~ +104°F) / 20% ~ 85% RH	
Mechanical	Dimensions (WxHxD)	300.0 x 47.0 x 208.7mm (11.81" x 1.85" x 8.22")	
	Weight (With hard disks)	1.47Kg (3.24 lb)	
Language		Korean, Japanese, Chinese (Simplified), English, French, German, Spanish (European), Italian, Russian, Polish, Czech, Turkish, Dutch, Portuguese (South American), Swedish, Danish, Thai, Romanian, Serbian, Croatian, Hungarian, Greek, Chinese (Traditional), Finnish, Norwegian (25 Language)	
KIT PACKAGE			
Dimensions (WxHxD)		445.0 x 218.0 x 306.0mm (17.52" x 8.58" x 12.05")	
Weight		4.51Kg (9.94 lb)	

SDC-9441BC

VIDEO		
Imaging Device / Effective Pixels		1/2.9" 2M CMOS / 1920(H) x 1080(V)
Scanning System		Progressive, 30fps (NTSC) / 25fps (PAL)
Synchronization / Min. Illumination		Internal / 0Lux (IR LED on)
Camera Output		1CH BNC, Maximum Transmission Length : 300m (75Ω 3C2V)
Min. Cable Length		60ft (18.3m) included
LENS		
Focal Length / Max. Aperture Ratio		4mm / F2.1
Angular Field of View		H : 72.2° / V : 52.9° (Tolerance range ±6%)
OPERATIONAL		
Shutter Mode / Gain Control		Auto (Rolling shutter) / Auto
White Balance / Digital Noise Reduction		Auto (1,800°K ~ 10,500°K) / 3D DNR
Flickerless / Day & Night		Auto / True Day/Night with ICR
IR Distance		25m (82ft)
ENVIRONMENTAL		
Operating Temperature / Humidity		-10°C ~ +50°C (+14°F ~ +122°F) / Less than 90% RH
Ingress Protection		IP66
ELECTRICAL		
Input Voltage / Power Consumption		12V DC / Max. 3.7W
MECHANICAL		
Color / Material		Front : Gray silver / PC, Body : White / PC, Bracket : White / ADC12
Dimensions (WxHxD) / Weight		142.6 x 61.9 x 61.8mm (5.61" x 2.44" x 2.43") / 191g (0.42 lb)

Design and specifications are subject to change without notice.



The ECO mark represents Hanwha Techwin's will to create environment-friendly products, and indicates that the product satisfies the EU RoHS Directive.

HEAD OFFICE

6, Pangyo-ro 319beon-gil, Bundang-gu, Seongnam-si, Gyeonggi-do, SEOUL 463-400 Rep. of KOREA
Tel : +82-70-7147-8753, 8764 Fax : +82-31-8018-3740 www.samsungsecurity.com www.samsungcctv.com
COPYRIGHT BY HANWHA TECHWIN. ALL RIGHT RESERVED

SAMSUNG TECHWIN AMERICA INC.
100 Challenger Rd, Suite 700 Ridgeland Park, NJ 07660
Toll Free : +1-877-213-1222 Direct : +1-201-325-6920
Fax : +1-201-373-0124
www.samsungs.com

SAMSUNG TECHWIN EUROPE LTD.
2nd Floor, No. 5 The Heights, Brooklands, Weybridge, Surrey, KT13 0NY, UK
Tel : +44-1932-82-6700 Fax : +44-1932-82-6701
www.samsungsecurity.co.uk

SHANGHAI SAMSUNG TECHWIN CO., LTD.
32F, Bk B, New Caohejing International Business Center, No. 391 Guiping Rd., Shanghai, China, 200233
Tel : +86-21-5427-1155 Fax : +86-21-5423-5122
www.samsungsecurity.cn

